SW405K5

PRODUCT SPECIFICATIONS

SANY



STANDARD FEATURES

- → Engine: Deutz TCD 7.8 (EU Stage 5)
- → Boom Suspension System
- → Locking Differential Axle
- → Automatic Transmission Kick Down
- → Bucket Self-Leveling and Return to Dig

- → SANYLive Telematics
- → Single Joystick Control
- → Third Function Hydraulics
- → Reversible fan
- → 360° View Camera

Gross Power

195 kW

Bucket Capacity
3.2 m³

Operating Weight 18 500 kg

Straight Turn Tipping Load
14500 kg

Full Turn Tipping Load
13100 kg

PRODUCT SPECIFICATIONS

1	Ground dearance
2	Height to Top of Cab
3	Center Line of Rear Axle to Edge of Co
4	Wheelhase

OVERALL DIMENSIONS

		STANDARD
1	Ground dearance	430 mm
2	Height to Top of Cab	3 580 mm
3	Center Line of Rear Axle to Edge of Counterweight	2 335 mm
4	Wheelbase	3 200 mm
5	Center Line of Front Axle to Center Pivot	1 600 mm
6	Shipping Length without Attachment	7 040 mm
7	Shipping Length with Bucket	8 180 mm
8	Max. Dump Height	5 415 mm
9	Hinge Pin Height at Max. Lift	4 145 mm
10	Dump Clearance at Max. Lift	3 100 mm
11	Dig Depth, Level Bucket	30 mm
12	Reach at Max. Lift and 45° Discharge	1185 mm
13	Roll Back at Max. Lift	58°
14	Dump Angle at Max. Lift and Dump	45°
15	Roll Back at Carry Height	50°
16	Roll Back at Ground	45°
17	Tail Angle to the Rear Wheel	27°
18	Clearance Circle to Outside of Tires	5 635 mm
19	Clearance Circle to Counterweight	5 911 mm
20	Max. Circle	6 465 mm
21	Width of the Bucket	3 015 mm
22	Width	2 200 mm
23	Articulation Angle	+/- 40°

In the interest of continual equipment development, SANY reserves the right to change these specifications at any time without prior notification.

SANY SW405K5

Machine Parameters

WEIGHT	
Operating Weight	18 500 kg
ENGINE	Deutz TCD7.8
Max Gross Power	195 kW
Rated power	170 kW
Max Gross Torque	1308 Nm
Displacement	7.8 L
OPERATING	
Bucket Capacity	3.2 m ³
Breakout Force	180 kN
Tipping Load Straight	14 500 kg
Tipping Load @ Full Turn	13 100 kg
Clearance (full lift 45° dump)	3100 mm
Reach (full lift 45° dump)	1185 mm
HYDRAULIC SYSTEM	
Max Flow	306.6 LPM
Max Pressure	28 MPa
HYDRAULIC CYCLE TIMES	
Raise	5.4 sec
Dump	1.9 sec
Float Down	3.3 sec
Total Cycle Time	10.6 sec
SERVICE CAPACITIES	
Fuel Tank	300 L
Cooling System	43 L
Engine Crankcase	23 L
Transmission	35 L
Front Axle	28 L
Rear Axle	28 L
Hydraulic Tank	290 L
DEF Tank	20 L
TRANSMISSION	
Shift Modes	Automatic, Manual, Kick Dow
Forward Gear 1–4	7.3/13.5/26/40 km/h
Reverse Gear 1-3	7.3/13.5/26 km/h
POWER TRAIN	
Front Axle	Fixed
Traction Aid	Manual Differential Lock
Rear Axle	Oscillating
Traction Aid	Open Differential
Service Brake	Wet Disk
Parking Brake	Disk Brake



PRODUCT EQUIPMENT

ENGINE Exhaust aftertreatment (DPF+SCR) Keyless start Engine emergency stop (in cab) P/E Patten Cold start aid (air pre-heated) Hydraulic-driven fan, regulated by temperature (Reversible rotation, manual) **POWER TRAIN** Gear selector lever (Steering-column) Fully automatic shifting 1-4, H/L Patten & Manual Automatic Transmission Kick Down Clutch-cutoff Service brake,4-wheel, wet-type, hydraulic brake Parking brake, Electronically controlled, hydraulic caliper disc brake Differential lock front axle (manual) **HYDRAULIC** Full variable load-sensing system with steering priority Single-lever joystick with F/R+KD+horn+3rd function valve roller) Secondary steering Dual brake pedals 3rd function valve Hydraulic quick coupler lines Ride contral system(Boom suspension system) Boom kick-out Bucket self-leveling and return to dig • **WORK TOOLS** 0 Bucket volume 3.2m3(Cutting edge, bolt-on) 0 Quick coupler **CABIN** Cab with ROPS / FOPS certification Steering wheel with turning signal control lever **Emergency hammer** Rear window, heated Rear mirrors, outside (2, foldable, heated), inside(1) Sun visor, front window Air-Suspension seat (cloth, heated) Seat belt, 2-point retractable Armrest adjustable in multiple directions Rear-view camera 360° view camera 7 inch smart color display Auto air conditioner **ELECTRICITY** Battery main switch 12-volt socket Cigarette lighter, 24V **USB** socket Bluetooth radio Back up alarm Travel acoustic alarm Travel strobe light alarm



Standard •

Optional O

^{*}Standard and optional equipment may vary. Consult your local dealer for details*



QUALITY CHANGES THE WORLD

SANY ITALIA S.R.L.

VIA DRUENTO 254/B VENARIA REALE (TO) - ITALY
TEL. 0118002130
HTTPS://WWW.SANYITALIA.COM

October 2022 Edition

Materials and specifications are subject to change without notice. Featrued machines in photos may include additional equipment. See your local dealer for available options please.